



H-series Column Type Semi-automatic - H-700



Standard Features

1. Power-driven blade cleaning brush and coolant cleaning flush hose.
2. Idle wheel motion?detector for blade jam/break shut-off.
3. Carbide guides suitable for bimetal and carbide tipped bands.
4. Hydraulic quick acting vise jaw for stock clamping.
5. Double vise jaws design, vise jaws clamp the material on both side of the saw blade.
6. Manual floating roller stock feed.
7. Hydraulic blade tension control.

STANDARD ACCESSORIES

1. Tools with tool box	1 set
2. 5 FT (1,5M) long roller table	1 set
3. Band-cleaning wire brush	2 pcs
4. Band saw blade	1 pc
5. Instruction manual and Parts list	1 copy

Optional Accessories

1. Beam light to show blade cutting line.
2. Variable blade speed drive.
3. Variable vise pressure system.
4. Amplifying valve for auto-adjusting cutting feed-rate.
5. Automatic chip conveyor.

<TD >82.105.138.180.230.260
VARIABLE SPEED 65-260 (OPT.)

SPECIFICATIONS / MODEL		H-700	
Cutting Capacity	mm	● 720	■ 800Wx 720H
	in	● 28	■ 31.5Wx 28H
Blade Size	mm	54 x1.6 x 8128	
	in	2 x 0.063 x 320	
Blade Speed	M/min	25.32.42.55.70.80	
	F/min	VARIABLE SPEED 20-80 (OPT.)	

Motor Output	hp	Blade 10, Hyd. 3, Coolant 1/8
	kw	Blade 7.5, Hyd. 2.2 Coolant 0,1
Shipping	mm	3200 x 1790 x 2560
Volume(L*W*H)	ft	10.5 x 5.8 x 8.4
Weight	kg	3500/4000
Net/Gross	lb	7700/8800



Gauteng Office: 29 Loper Avenue, Aeroport, Spartan ext.2, 1619, Kempton Park
Eastern Cape Office: 26a Mangold Street, Newton Park, 6045

T: +27 11 392 3710 | F: +27 11 392 3711
T: +27 41 363 8535 | F: +27 41 363 8536

info@skok.co.za | www.skok.co.za