



BS Series Pivot Type Full Automatic - BS-300 GA-HAS



Standard Features

1. Precise cut off length setting.
2. Auto head-elevation and quick approach.
3. Nesting fixture.
4. Quick-action hydraulic twin -vise (split)3-jaw clamping.
5. Unique two-way carriage vise jaw.
6. Cutting piece counter.
7. Multiple stroke counter.
8. LED blade speed display.
9. Power-driven saw-band brush.
10. Quick adjusting carbide saw-band guides.
11. Idle wheel motion detector.
12. Hydraulic band-tension control.
13. Coolant cleaning flush hose.
14. Work-area light.

Standard Equipment

1. Tools with tool box	1 set
2. 7 ft .(2M) long roller table with vertical rollers	1 set
3. Band-Cleaning wire brush	1 pc
4. Bandsaw blade	1 pc
5. Instruction Manual	1 copy

Select Equipment

1. Automatic chip conveyor.
2. Variable blade-speed drive.
3. Variable vise pressure system.
4. Amplifying valve for auto-adjusting cutting feed-rate.
5. Additional spare roller table, wire brush, saw blade, work-area light, etc.
6. GA Numeric control.

SPECIFICATIONS / MODEL		BS-300HAS/GA
Cutting Capacity	mm	330 350Wx250H or 300Wx300H
	in	13 13Wx10H or 12Wx12H
Bundle Cutting (W*H)	mm	250Wx165H
	in	10Wx6.5H
Blade Size	mm	34Wx1.10x3820L
	in	1.34Wx0.043x150L
Blade Speed	M/min	25,32,42,55,70,80 Variable Speed 20-80 (Opt.)
	F/min	82,105,138,180,230,260 Variable Speed 65-260 (Opt.)
Motor Output	HP	Blade 5 ; Hyd.1 ; Coolant1/8
	KW	Blade 3.7 ; Hyd. 0.75 ; Coolant 0.1
Shipping Volume (L*W*H)	mm	2120 x 2090 x 1600
	ft	6.9 x 6.8 x 5.3
Weight Net / Gross	kg	1410/1640
	lb	3102/3608

MOTOR MODEL	SAW BLADE				HYDRAULIC	COOLANT
	50HZ	60HZ	50HZ	60HZ		
BS300HAS/GA	5HP x 4P	5HP x 4P	Variable Speed 5HP x 4P	Variable Speed 5HP x 4P	1HP x 4P	1/8 HP